



# SAGE OIL VAC **PM TRAILER**

## MODEL 1C5H-3

The 1C5H-3 trailer is one of Sage Oil Vac's most popular models. Its tandem-axle design works well in oil and gas service and off-road use. With two fresh product tanks and one used oil tank, this trailer works great for oil changes and antifreeze top offs. The open trailer design also optimizes load conditions, tongue weight and axle weight for a safer transport to your jobsite.



## TANKS

- (1) 250 gallon ( 946 l )ASME tank used oil
- (1) 250 gallon (946 l )ASME tank fresh oil & fluid
- (1) 120 gallon (454 l)ASME tank fresh oil & fluid

## POWER

- 12.5 CFM vacuum/compressor driven by 5.5 hp electric start Honda gas engine – 125 psi max



## HOSES & REELS

- (1) 1 in in x 50 ft (2.54 cm x 15.2 m) used oil hose on spring retractable reel
- (2) 3/4 in x 50 ft (1.905 cm x 15.2 m) fresh oil hose on spring retractable reel
- 3/8 in x 25 ft (0.9525 cm x 7.6 m) air hose on spring retractable reel (priced separately)
- 1 1/2 in x 20 ft (3.81 cm x 6.1 m) used oil offload hose (priced separately)

## SAGE OIL VAC ATTRIBUTES

- Patented vacuum process to load fresh fluid tanks (Barrel Straws priced separately — specify quantity and length)
- Patented used Filter Receptacle
- Patented Filter Stinger (priced separately)
- 25 micron filters on all new oil reels

## HOSE ENDS, METERS, HANDLES

- Used oil hose — 1 in (2.54 cm) cam and groove fitting
- Fresh fluid hoses — 1/2 in (1.27 cm) flush face quick disconnects, adaptable to meters (priced separately, specify quantity and type)

## FRAME

- Trailer mounted
- Tandem 5200 lb leaf spring axle with electric brakes
- (4) 225/75R15 tires
- Universal 2 5/16 in hitch
- Drop leg jack
- Tongue-mounted toolbox (43 in W x 16 in D x 24 in H)
- DOT-approved light package
- 7 plug electric adapter

## DIMENSION & WEIGHTS

- Width: 86.125 in (2.06 m)
- Length: 221.06 in (5.61 m)
- Empty weight: 3595 lb (1630.66 kg)
- Normal max operating weight: 6333 lb (2872 kg)