



SAGE OIL VAC **PM TRAILER**

MODEL 1C5I-4

The four-tank 1C5I-4 trailer model has two primary set ups: two tanks for new and used oil and two tanks for new and used antifreeze for large engine oil/antifreeze exchanges or three new fluid tanks with one used tank. The open trailer design optimizes load conditions, tongue and axle weight for a safer transport to your jobsite.



TANKS

- (1) 120 gallon (454 l)ASME tank used oil
- (3) 120 gallon (454 l)ASME tank fresh oil & fluid

POWER

- 22 CFM vacuum/compressor driven by 8 hp electric start Honda gas engine – 125 psi max



HOSES & REELS

- (1) 1 in in x 50 ft (2.54 cm x 15.2 m) used oil hose on spring retractable reel
- (3) 3/4 in x 50 ft (1.905 cm x 15.2 m) fresh oil hose on spring retractable reel

SAGE OIL VAC ATTRIBUTES

- Patented vacuum process to load fresh fluid tanks (Barrel Straws priced separately — specify quantity and length)
- Patented used Filter Receptacle
- Patented Filter Stinger (priced separately)
- 25 micron filters on all new oil reels

HOSE ENDS, METERS, HANDLES

- Used oil hose — 1 in (2.54 cm) cam and groove fitting
- Fresh fluid hoses — 1/2 in (1.27 cm) flush face quick disconnects, adaptable to meters (priced separately, specify quantity and type)

FRAME

- Trailer mounted
- Tandem 5200 lb leaf spring axle with electric brakes
- (4) 225/75R15 tires
- Universal 2 5/16 in hitch
- Drop leg jack
- Tongue-mounted toolbox (24 in W x 16 in D x 43 in H)
- DOT-approved light package
- 7 plug electric adapter

DIMENSION & WEIGHTS

- Width: 86.125 in (2.19 m)
- Length: 234.5 in (6 m)
- Empty weight: 4037 lb (1831 kg)
- Normal max operating weight: 7600 lb (3447 kg)