



SAGE OIL VAC **PM TRAILER**

MODEL 1C6G-2

Large capacity oil changes are made easy with the 1C6G-2 trailer. The trailer setup features a 390-gallon used oil tank and 390-gallon new oil tank for those diesel generators that hold 100 gallons or more. The open trailer design also optimizes load conditions, tongue weight and axle weight for a safer transport to your jobsite.



TANKS

- (1) 390 gallon (1476 l) ASME tank used oil
- (1) 390 gallon (1476 l) ASME tank fresh oil & fluid

POWER

- 12.5 CFM vacuum/compressor driven by 5.5 hp electric start Honda gas engine – 125 psi max



HOSES & REELS

- (1) 1 in in x 50 ft (2.54 cm x 15.2 m) used oil hose on spring retractable reel
- (1) 3/4 in x 50 ft (1.905 cm x 15.2 m) fresh oil hose on spring retractable reel

SAGE OIL VAC ATTRIBUTES

- Patented vacuum process to load fresh fluid tanks (Barrel Straws priced separately — specify quantity and length)
- Patented used Filter Receptacle
- Patented Filter Stinger (priced separately)
- 25 micron filters on all new oil reels

HOSE ENDS, METERS, HANDLES

- Used oil hose — 1 in (2.54 cm) cam and groove fitting
- Fresh fluid hoses — 1/2 in (1.27 cm) flush face quick disconnects, adaptable to meters (priced separately, specify quantity and type)

FRAME

- Trailer mounted
- Tandem 5200 lb leaf spring axle with electric brakes
- (4) 225/75R15 tires
- Universal 2 5/16 in hitch
- Drop leg jack
- Tongue-mounted toolbox (24 in W x 16 in D x 43 in H)
- DOT-approved light package
- 7 plug electric adapter

DIMENSION & WEIGHTS

- Width: 95.63 in (2.43 m)
- Length: 212.63 in (5.40 m)
- Empty weight: 3825 lb (1735 kg)
- Normal max operating weight: 7520 lb (3411 kg)