



# SAGE OIL VAC **SERVICE SKIDS**

## MODEL 2M34-2100

The 2M34-2100 service skid is a great unit to get started in onsite oil changes. The skid is a spin-off of the 2M32-2101, we added a bigger compressor to be able to give this skid more versatility in the field.



## TANKS

- (1) 30 gallon (114 l) ASME tank used oil
- (1) 30 gallon (114 l) ASME tank fresh oil & fluid

## POWER

- 12 CFM vacuum/compressor driven by 6 hp gas engine



## HOSES & REELS

- (1) 3/4 in x 25 ft (1.905 cm x 7.6 m) used oil hose on spring retractable reel
- (1) 5/8 in x 25 ft (1.905 cm x 7.6 m) fresh oil hose on spring retractable reel
- Integrated used oil offload

## SAGE OIL VAC ATTRIBUTES

- Patented vacuum process to load fresh fluid tanks (Barrel Straws priced separately — specify quantity and length)
- Patented used Filter Receptacle
- Patented Filter Stinger (priced separately)
- 25 micron filters on all new oil reels

## HOSE ENDS, METERS, HANDLES

- Used oil hose — 3/4 in (1.905 cm) cam and groove fitting
- Fresh fluid hoses — 1/2 in (1.27 cm) flush face quick disconnects, adaptable to meters (priced separately, specify quantity and type)

## FRAME

- Skid mounted
- Table top frame design
- Forklift-able (empty only)

## DIMENSION & WEIGHTS

- Width: 41.25 in (1.05 m)
- Length: 58.38 in (1.48 m)
- Height: 48.81 in (1.24 m)
- Empty weight: 775 lb (351.5 kg)
- Normal max operating weight: 1213 lb (550.2 kg)